

A0

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **02241296 A**

(43) Date of publication of application: **25.09.90**

(51) Int. Cl. **H04R 5/02**
B60R 11/02
H04R 1/02

(21) Application number: **01062522**

(22) Date of filing: **15.03.89**

(71) Applicant: **MATSUSHITA ELECTRIC IND CO LTD**

(72) Inventor: **SERIKAWA MITSUHIKO**
ISHIHARA SUMIO
YAMADA KATSUSHI
SATO KATSUMASA

(54) **CAR AUDIO DEVICE**

(57) Abstract:

PURPOSE: To prevent stereoscopic feeling from being damaged by arranging a pair of main speaker on right and left sides in a forward part in a vehicle and arranging plural center speakers near the center of a pair of the main speakers with being respectively directed to a driver seat and an assistant seat.

CONSTITUTION: In a driver seat 1, since distances from the driver seat 1 to both right and left channels speakers 4 and 3 are widely different, a sound image is made normal in a position biased to the right speaker 4. However, the lowering of a level in a left channel signal reproducing tone is compensated by reproducing a left channel signal by a center speaker 6 for driver seat. Thus, the sound image biased to a right side can be made normal to the front. Next, in the assistant seat 2, oppositely to the operation as mentioned above, the lowering of the level in a right channel signal 1 reproducing tone is compensated by reproducing a right channel signal by a center speaker 5 for assistant seat. Thus, the sound image biased to the left side can be made normal to the front.

COPYRIGHT: (C)1990,JPO&Japio

